




Welcome to

PlexiSystems



- Our Commitment
- Products
- Company
- Customer Support
- Contact Us

PlexiSystems Dealer List

Register your PlexiSystem product

Home

PlexiOne

PlexiSystems PlexiOne Tube Direct Box

- Individual Discreet Power Supplies
- 3 Dual Triode tubes
- Jensen Input and Output transformers
- Hammond power transformers
- Combo XLR/1/4" Inch input connectors
- Adjustable Gain
- Superior bandwidth

PlexiOne Specifications

- Circuit Topology: XXXXXXXXXXXX
- Gain: maximum gain +XXdB
- Input Impedance:XXXX ohm unbalanced (single ended)
- Maximum Input Level +24dBu unbalanced, 400w speaker input
- Output Connectors (2): XLR type, pin 2 hot electronic balanced
- Maximum Output Level (Class A): +XXdBu DC coupled, balanced 600 ohms (mic and line out)
- Noise 20kHz Unweighted: -100dBu minimum gain position
- Distortion THD, IMD: 0.1% at +10dB
- Frequency Response, +/-0.5dB: 5Hz to 100kHz
- Frequency Response, -3dB: 1Hz to 500kHz (input band limited)
- AC Power: Internal toroidal AC supply
- Dimensions: XX x XX x XX in (XXX x XX x XXXmm)
- Weight-Packed: XXlbs (XXkg)

Click [HERE](#) to download the PlexiOne direct box PDF.

Click [HERE](#) to download sound samples.

